CERTIFICATE OF LOCATION OF GOVERNMENT CORNER Northeast Corner of Section 13, Township 114N, Range 40W, 5th P.M.							
N	ortheast	Corner of Sec	tion	_,Township	,Rar	ige40	, <u>5th</u> P.M.
STATE OF MINNESOTA, County ofYellow Medicine							
At the corner location shown on the sketch:							
	On found a						
	☐ left monument as found, ☐ lowered monument, ☐ removed monument (explain)						
X	On June 6,1973 DATE over iron pin.	placed a <u>Minn</u>	esota High	way Depar	tment cast	iron mo	nument (flush)
SKETCH OF REFERENCE TIES							
4-N-	Saint	Orci	RD	 ,	MHD CO IN WES (N.W. S	OPPER 1 ST POW IDE, UP	NAIL & DISC ER POLE N.N.E. 3.0).
	0505:01:	10, 81		 		•••	
	SECTION TII4N	12 R40W		\ <u>`</u> ॐ _y	SECTION TILAN		7 R39W
			$\rightarrow \bigcirc \downarrow$	<u></u> _			
		61,89			C.S.A.H. NO		
		LE CAP IN TE IE POLE S.W. (UP 2.0)			1,6	8 DIS	COPPER NAIL C IN POWER S.E. (N.E. SIDE, .O).
	SECTION TILLAN	13 R40W		SEÇT	ION'	À	18 R39W
Statement of evidence relative to this corner location is on back of page.							
I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision. Signature				OFFICE OF THE REGISTER OF DEEDS County of Yellow Medicine I hereby certify that this document was filed in the Reg. of Deeds office at			
☐ County Surveyor, ☐ County Engineer				OCUMENT	NO	F- 6 1	<u> </u>

M.H.D. FORM NO. 2105

Statement of Evidence: NORTHEAST CORNER SECTION 13, T114N, R40W

The original Public Land Survey was run in 1858 and a wood post was set in a mound with pits to mark the corner.

In 1884 Jonah Peterman found a stone at the corner.

Peterman also located the stone in 1890.

In 1901 John Norgaard, County Surveyor, found the stone inplace, used it in platting Hanley Falls and replaced it with a 6 inch x 6 inch x 24 inch Jasper monument.

County Ditch #41 was built in the 1940's.

The Yellow Medicine County Highway Department found the monument, date unknown.

In 1971 the Minnesota Highway Department excavated 6 feet x 6 feet x 6 feet deep at the road intersection. No evidence of monumentation could be found.

An analysis of the record data compared to 1972 & 1973 field measurements indicates the derivative location of the section corner. The derivative location is on centerline of north-south road and at P.I. in east-west road 0.5 feet north of centerline.

For details of survey analysis and 1972 electronic survey measurements, see Survey Report for S.P. 4203 and 8701 on file in the Surveys Section, Minnesota Highway Department, Willmar, Minnesota.