


# CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

Northeast Corner of Section 11, Township 115N, Range 44W, 5th P.M.  
STATE OF MINNESOTA, County of Yellow Medicine

At the corner location shown on the sketch:

- On \_\_\_\_\_ found a \_\_\_\_\_  
DATE
- left monument as found,  lowered monument,  removed monument (explain)
- On 12/16/76 placed a Minnesota Highway Department cast iron  
DATE monument with brass plate stamped.

### SKETCH OF REFERENCE TIES



Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

Richard M Knudsen 1-17-77  
SIGNATURE DATE

Registration No. 11526

- Land Surveyor,  Professional Engineer
- County Surveyor,  County Engineer

OFFICE OF THE REGISTER OF DEEDS  
County of \_\_\_\_\_ COUNTY RECORDER  
YELLOW MEDICINE COUNTY

RECORDED  
GRANTOR  
GRANTEE  
INDEXED

I hereby certify that this document was filed in the Reg. of Deeds office at 9:45 A.M. on the 21 day of March A.D., 19 77

Register of Deeds Norman J. Opdahl

By Kay Nordahl COUNTY RECORDER  
YELLOW MEDICINE COUNTY Deputy

DOCUMENT NO. 158923

Statement of Evidence: Northeast Cor., Sec. 11, Township 115N, Range 44W

The original Public Land Survey was run in 1871 and a post set in a mound to mark the original corner.

In 1901, J. Norgaard, County Surveyor, found stone and stake in mound. Placed a 6"x6"x24" Jasper stone monument.

In 1929, Minnesota Highway Department field notes indicate a 6"x8" stone monument was found 1 foot below the surface.

In May 1930, D. F. Mattson, MHD Project Engineer, found a 6"x6" Jasper stone monument and placed two 3"x3" Iron Pipe reference ties.

In 1934, the County Engineer found the stone monument and reference ties.

In 1959, the Minnesota Highway Department found the Jasper stone monument.

On December 16, 1976, the Minnesota Highway Department placed a cast iron monument using information and ties from right-of-way map and final grading plans. Top of monument is down 2" below the surface.

An analysis of the record data indicates the cast iron monument set by the Minnesota Department of Transportation is accepted as the location of the Public Land Survey corner.