CERTIFICATE OF LOCATION OF GOVERNMENT CORNER NORTHWEST Corner of Section 30 Township 113 N, Range 39 W, 5 th P.M. STATE OF MINNESOTA, County of YELLOW MEDICINE	
At the corner location shown on the sketch:	
On 10-23-85 found a 6"x6"x24" GRANITE BLOCK DOWN 0.6"	
■ left monument as found, □ lowered monument, □ removed monument (explain)	
On 10-23-85 placed a 11/4"x 11/4"x 20" PERFORATED STEEL TUBE WITH ALUMINUM CAP STAMPED DNR SURVEY MARKER, OVER TOP	
SKETCH OF REFERENCE TIES	
NOTE: MONUMENT IS 7' NORTH OF FIELD DIV. EAST 5' SOUTH OF FIELD DIV. WEST NOTE: MONUMENT IS 7' NORTH OF FIELD DIV. EAST 5' SOUTH OF FIELD DIV. WEST DIVISION NO TIES AVAILABLE	
Statement of evidence relative to this corner location is on back of page. JAG 12-6-85 G-1187	
I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision. I hereby certify that this document was filed in the Co. Recorders of fice at 9:25 A:M. on the 21 day of March A.D., 19 86 Registration No. 17005 County Recorder Norman J. Opdahl	
Registration No	By Kay Nerdahl Deputy
☐ County Surveyor, ☐ County Engineer	DOCUMENT NO. 188026 GRANTOR GRANTES
Mn/901-7105 (4.77)	- HEETER

Northwest Corner Section 30, Township 113 North, Range 39 West

This corner was originally established by the U. S. General Land Office survey in 1858. The government notes show corner marked with a wood post set in mound of earth with pits and trench dug around the mound.

In July 1985, the DNR Bureau of Engineering contacted the following for corner information:

Lyon County Offices of the Recorder and Highway Engineer Yellow Medicine County Offices of the Recorder and Highway Engineer

The following information was obtained from the Yellow Medicine County Recorder's Office:

Surveyor's Record Book B, on Page 217, contains a collection of what was found at government corners by John Norgaard, County Surveyor, dated September 27, 1901. Norgaard states he found a stake and stone at fence corner set by Lyon County. A 6" by 6" by 2 foot jasper granite stone was set 2" above ground at this location.

Surveyor's Record Book, on Page 263, contains a survey by John Norgaard, County Surveyor in March 1912. Norgaard states he found the stone he set 12 or 13 years ago, and shows a distance of 2647 feet from this corner to the east quarter corner of Section 24.

In October 1985, the DNR Bureau of Engineering traversed to the area of the corner and found a 6" by 6" by 24" cut granite stone down 0.6 feet. Stone is:

on field divisions north and south

- ± 7 feet north of field division east
- ± 5 feet south of field division west

Accept the found stone as marking the location of the corner.

Traverse information is available from the DNR Bureau of Engineering.

200hab/missu4