moex No. 55-75	
CERTIFICATE OF LOCATION	OF GOVERNMENT CORNER
North quarter Corner of Section	29 ,Township 114 ,Range 40 , 5th P.M.
STATE OF MINNESOTA, County ofYellow Medicine	
At the corner location shown on the sketch:	
☑ On 9-12-2000 found a stone 3' below the road surface	
☐ left monument as found, ☐ lowered monument, ☐ removed monument (explain)	
☑ On 9-12-2000 placed a 5/8" iron rerod with a seal #11943 over the stone at road surface.	
SKETCH OF REFERENCE TIES	
79.87' Nail and seal in power pole 79.87' Northwest	
Statement of evidence relative to this corner location is on back of page.	
I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision. Compared to the data contained herein was prepared by me or under my direct supervision. Compared to the data contained herein was prepared by me or under my direct supervision. Compared to the data contained herein was prepared by me or under my direct supervision. Compared to the data contained herein was prepared by me or under my direct supervision. Compared to the data contained herein was prepared by me or under my direct supervision. Compared to the data contained herein was prepared by me or under my direct supervision. Compared to the data contained herein was prepared by me or under my direct supervision. Compared to the data contained herein was prepared by me or under my direct supervision. Compared to the data contained herein was prepared by me or under my direct supervision. Compared to the data contained herein was prepared by me or under my direct supervision. Compared to the data contained herein was prepared by me or under my direct supervision. Compared to the data contained herein was prepared by me or under my direct supervision. Compared to the data contained herein was prepared by me or under my direct supervision. Compared to the data contained herein was prepared by me or under my direct supervision. Compared to the data contained herein was prepared by me or under my direct supervision. Compared to the data contained herein was prepared by me or under my direct supervision. Compared to the data contained herein was prepared by me or under my direct supervision. Compared to the data contained herein was prepared by me or under my direct supervision. Compared to the data contained herein was prepared by me or under my direct supervision. Compared to the data contained herein was prepared by me or under my direct supervision. Compared to the data contained herein was prepared by me or under my direct supervision. Compare	OFFICE OF THE COUNTY RECORDER County of I hereby certify that this document was filed in the Co. Recorders office at 11:10 A .M on the 13 day of August A.D. ***92001 County RecorderKay Nerdah1
☑ Land Surveyor, ☐ Professional Engineer ☐ County Surveyor, ☐ County Engineer	By Sail RONGK Deputy DOCUMENT NO. 226600

Statement of Evidence

On September 12, 2000 Moseng Land Surveying dug with backhoe and found a stone 3 feet below the road surface. Two rerod were placed next to the stone. A 5/8" rerod with a seal was set over the stone at the road surface, using 12' ties SW and NW.