	Cl	ERTIFICATE OF LOCATI	ON OF GOVERNMENT CORNER						
	N	1/4 Corner of Section	32, Township <u>114N</u> , Range <u>38W</u> , <u>5TH</u> P	.М.					
ļ	STATE	TATE OF MINNESOTA, County of YELLOW MEDICINE							
l	At the	corner location shown on the	ne sketch :						
	⊠ On	07-21-06 found NOTH	ING						
l									
		☐ left monument as found, ☐ lowered monument, ☐ removed monument (explain)							
	⊠ <u>0</u> n	07-26-06 placed 3/	4" IRON PIPE WITH YELLOW CAP #22422	_					
Ì		WN 0.5'	_						
Ì				<u> </u>					
	1	reference ties							
SECTION 29									
	1	, W							
Ì	-Ŋ-	TILLED	L I NE						
		<b>,</b>	SDOOM ELD LI						
İ		MAG NAIL ON SW SIDE { OF PP UP 1.4' {	H						
	1 4	- 51.29 <sup>ل</sup> ِ	OCD						
		CDAVEL (TWO DO )	<del></del>						
		GRAVEL (TWP. RD.)  C/L 170TH AVE—	· <del>\$</del>						
			\ \ \—————————————————————————————————						
		OREB V 1/2" REBAR W/ 25.55'	29.82' 1/2" REBAR W/						
		1/2" REBAR W/ 25.55' YCA TRAV. CAP							
			YCA TRAV. CAP						
		T71.1 CD	ਰ TILLED						
		TILLED							
SECTION 32									
						Statemen	nt of evidence relative to this corner	location is on back page	
						I hereb	y certify that this document and the	OFFICE OF THE COUNTY RECORDER	
	1	entained herein was prepared by me	County of						
	ana und	ler my direct supervision.	I hereby certify that this document was file	ed					
	Lon	-clas D Kygo 8-2-06	in the Co. Recorder office atM on the day of A.D.,20						
	D = 1	Signature Date							
	1	ation No. <u>22422</u> and surveyor,□Professional Engineer		— ::tv					
		ounty Surveyor,□ County Engineer	DOCUMENT NO.	- · y					
	i	CHILLY DON FOTOLS - COUNTY LINGTHOOL							

NC Yaggy Colby Assoc. Inc. 1270 Northland Dr. Svite 150 Mendata Heights. Mr 55120 Doc# 241404 Fee: \$.00 2 Pages

Office of County Recorder Yellow Medicine County, Minnesota I hereby certify that the within instrument was filed on September 14, 2006 at 09:55 AM

# **Statement of Evidence**

BY Neids & Bakkelung Deputy

NORTH QUARTER CORNER OF SECTION 32, TOWNSHIP 114 NORTH, RANGE 38 WEST,  $5^{\text{TH}}$  P.M

#### October 1864:

Chase Davis & J.W. Webb Jr., Deputy Surveyors, set a post in mound with pits for the corner during the Original Public Land Survey.

## July 17, 1926:

John Norgaard, County Surveyor, indicated ties to the Northwest and Northeast Corners of Section 32, and reports equal distances of 2655 along the north line, but does not indicate any monument at the Quarter Corner.

## May 2006:

Isaiah Reicks, Yaggy Colby Associates, searched with a metal detector in the vicinity of the North Quarter corner and found nothing. Fence lines were located for 1 mile north. Field lines and found pipes were located for 1 mile south. These occupation lines projected within 0.8 feet of each other at a position 18 feet east of midway and online between the Northwest and Northeast Corners of Section 32.

### June 21, 2006:

Mark Haselius, Yaggy Colby Associates, dug with a backhoe in the gravel road at a point midway and on line as described above. Excavated a rectangular area 3 feet north-south by 8 feet east-west to a depth of 2.8 feet which is below natural ground, and found nothing. Also dug with a backhoe at a point in the center line of the road in line with an old fence line running north. Excavated a rectangular area 5 feet north-south and 9 feet east-west to a depth of 2.7 feet, which is below natural ground and found nothing.

#### June 26, 2006:

Isaiah Reicks, Yaggy Colby Associates, set a ¾" iron pipe with yellow cap in the center line of the gravel road at intersection of fence line running north. An analysis of record and survey data indicates that the existing occupation lines are the best evidence available to re-establish the obliterated corner, and the set iron pipe is accepted as a perpetuation of the Public Land Survey. For more information regarding this survey, contact Yaggy Colby Associates, Rochester, MN.