Index	Na	
muex	INO.	*******

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER			
E 1/4 Corner of Section 11 To STATE OF MINNESOTA, County of YELL At the corner location shown on the ske	OW MEDICINE etch		
Date □ left monument as found, □ lowere ☑ On4-28-09placed a	ed monument removed monument(explain) MAGNETIC NATI		
Date	WANTE IN THE STATE OF THE STATE		
SKETCH OF RE	FERENCE TIES		
Δ Φ	NE COR. SEC. 11 T-116, R-41		
N			
W 1/4 COR. SEC. 11 TO SEC. 11	S 0°01'47" E		
W 1/4 COR. SEC. 11 T-116, R-41 S 88°56'09" W 5292.07 FOUND RAIL ROAD SPIKE FOUND RAIL ROAD SPIKE S 88°56'09" W 5292.07 FOUND RAIL ROAD SPIKE S 88°56'09" W 5292.07 FOUND RAIL ROAD SPIKE S 88°56'09" W 5292.07 FOUND RAIL ROAD SPIKE R 7.170 N			
	SE COR. SEC. 11 T-116, R-41		
Statement of evidence relative to this corner location is on back of page.			
I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.	OFFICE OF THE COUNTY RECORDER County of		
Signature Date	I hereby certify that this document was filed in the County Recorders office at		
Registration No42300	County Recorder		
	By, Deputy		
□ Professional Engineer,□ County Engineer.	DOCUMENT NO		

STATEMENT OF EVIDENCE:

EAST QUARTER CORNER OF SECTION 11, TOWNSHIP 116 N, RANGE 41 W, YELLOW MEDICINE COUNTY, MINNESOTA

MAY 12 1892 - JONAH PETERMAN (COUNTY SURVEYOR) MADE A RETRACEMENT SURVEY OF SECTION 11, TOWNSHIP 116N, RANGE 41W. HE REPORTS ALL SECTION CORNERS AND QUARTER SECTION CORNERS FOUND, EXCEPT THE WEST QUARTER CORNER. HE SHOWS A DISTANCE OF 40.22 CHAINS TO THE NORTHEAST CORNER AND 40.76 CHAINS TO THE SOUTHEAST CORNER. NO TIES WERE RECORDED.

1974 COUNTY ENGINEERS PLANS FOR COUNTY ROAD NO. 8 SHOWS A MONUMENT AT THE SOUTHEAST CORNER OF SECTION 11 AND THE NORTHEAST CORNER OF SECTION 11. STATIONING SHOWS A DISTANCE OF 5346.90 FEET BETWEEN CORNERS. TIES SHOWN ON PLANS

JUNE 14, 1996 BYRON DAHLE PERFORMED A SURVEY IN SECTION 11. HE SHOWS A FOUND IRON MONUMENT AT THE SOUTHEAST CORNER AND A FOUND IRON MONUMENT AT THE NORTHEAST CORNER. HE SET A RAIL ROAD SPIKE AT LOST POSITION ON A STRAIGHT LINE AND SPLIT. HE SHOWS A BEARING AND DISTANCE OF N 0°01'47" W, 2673.82 FEET TO THE NORTHEAST CORNER AND A BEARING AND DISTANCE OF S 0°01'47" E, 2673.82 FEET TO THE SOUTHEAST CORNER. TIES MADE BUT NOT RECORDED.

DECEMBER 3, 2007 ROY A. MARIHART PERFORMED A SURVEY OF SECTION 11. HIS SURVEY SHOWS FOUND IRON MONUMENTS AT ALL CORNERS. HE SHOWS A BEARING AND DISTANCE OF N 01°01'48" E, 2673.60 FEET TO THE NORTHEAST CORNER AND A BEARING AND DISTANCE OF S 01°01'54" W, 2673.63 FEET TO THE SOUTHEAST CORNER. NO TIES RECORDED.

APRIL 28, 2009- BENJAMIN C. O'MALLEY PERFORMED A SURVEY IN SECTION 11. I FOUND A RAIL ROAD SPIKE AT THE CENTERLINE OF COUNTY ROAD 8 THAT VERIFIED BYRON DAHLE'S DISTANCE TO THE NORTHEAST CORNER AND THE SOUTHEAST CORNER. IT IS MY OPINION THAT THE ORIGINAL CORNER LOCATION IS NOT LOST AND SHOULD BE PLACED AT A PRORATED POSITION USING THE DIMENSIONS FROM THE SURVEY PERFORMED BY JONAH PETERMAN (COUNTY SURVEYOR) IN 1892. I SET A P.K. NAIL AT THIS POSITION AND MADE NEW TIES.

Doc# 248085 Fee: \$0.00 2 Pages

Office of County Recorder Yellow Medicine County, Minnesota I hereby certify that the within instrument was filed on May 7, 2009 at 9:15 AM

N_C
O'Malley & Boe Land Surveyors, Inc.
328 SW 3rd St.
Willmar, MN 56201

Kay Zempel, Yellow Medicine County Recorder

i Jbakkelund

__ Deputy