Doc# 257568 Fee: \$0.00 2 Pages

Property & Public Services
Property Records Division
Yellow Medicine County, Minnesota
I hereby certify that the within instrument
was filed on April 30, 2013 at 10:40 AM

Janel Timm, Yellow Medicine County Recorder

By Dalera Blood

_ Deputy

N/C BONNEMA SURVEYS INC PROFESSIONAL LAND SURVEYING 1809 22ND STREET SW, SUITE 104 WILLMAR, MN 56201

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER	
Northeast Corner of S	Section 33 , Township 114 , Range 44
Fifth Principal Meridian, State of Minnesota	, County of Yellow Medicine
At the corner location shown on the sketch:	
X On July 10, 2012 found a ½"x 15" Iron	Pipe and a 7" x 7" x 27" Chiseled Granite Stone at a depth of 2.3'
left monument as found □ lowered monument X removed monument (explain) Non Aug. 8, 2012 placed a Cast Iron Capped 2" by 30" square Telspar Monument (shown below as) DATE at the location of the found chiseled Granite Stone	
Section 28	Nail and Cap on Power Pole' Section 27 Edge of Road
	Township Road
Section 33 Top Center of Telephone Pedestal	Fire Number Sign The Teleper measurement is 0.6 North and 0.1' Best of the location of the W from Pipe (now removed) Project Coordinates (I you County Coordinates 1996 Adjustment)
Yellow Medicine County Coordinates (1996 Adjustment)	Project Coordinates (Lyon County Coordinates 1996 Adjustment)
N= 137927.50 E= 433929.06	N= 264159.01 E= 420914.04 is corner location is on back of this page.
I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision	
and that I am a duly Licensed Land Surveyor under the laws of the state of Minnesota.	
Signature	Typed or Printed Name: Duane A. Bonnema
Date $A/29/2013$	Reg. No

STATEMENT OF EVIDENCE

Northeast Corner Section 33, T114N-R44W

1871

L. Harrington was contracted by the United States Government Land Office to perform the Original Public Land Survey in this township. He records in his field notes, "Set a post for the corner to sections 27, 28, 33 \pm 34 raised mound as per instructions."

1899-1901

John Norgaard, County Surveyor, records in County Surveyor's Record Book B, Page 189, "Located according to breaking as was done when the government corner, were plain. Set top of monument level with ground."

July 7 \$ 8, 1903

John Norgaard, County Surveyor, records in County Surveyor's Record Book, Page 176, dimensions to this corner position, but does not mention what type of monument he found.

Sept 1917

C.W. Lamphere, Civil Engineer, prepared the record plat entitled "Plat of Sec 33, T. I I 4N, of R.44W. of 5th P.M." On this document he notes a "Stone as found" and dimensions to this corner position.

Unknown

The Yellow Medicine Co Hwy Dept corner tie book, Wergeland Twp, shows that they recorded 9 section corner witness ties, but does not mention what type of monument they found.

1972

The Minnesota Department of Natural Resources prepared a drawing entitled "Antler Wildlife Management Area." On this drawing they note "Stone In place" and dimension to this corner position.

July 17, 2012

Duane A. Bonnema, LS 14895, while doing a re-monumentation survey for the Minnesota Department of Transportation excavated a 4.5' deep hole which covered an area extending 7.5' northeast, 3.0' southwest, 3.0' southwest, and 3.0' northwest of this section corner location. At a depth of 0.2' a $\frac{1}{2}$ "x15" Iron Pipe was found. At a depth of 2.3', a 7"x7"x27" Square Quarried stone was found. This stone is evidently the stone set by Norgaard in 1900±. A MnDOT Cast Iron capped 2"x30" Telspar Monument was placed at the position of the found 7"x7"x27" Square Quarried Stone. The telspar monument was set 0.6' North and 0.1' East of the $\frac{1}{2}$ " iron pipe found near the surface (now removed).