

N/C  
 BONNEMA SURVEYS INC  
 PROFESSIONAL LAND SURVEYING  
 1809 22ND STREET SW, SUITE 104  
 WILLMAR, MN 56201

Janel Timm, Yellow Medicine County Recorder  
 By Debra Blood Deputy

<b>CERTIFICATE OF LOCATION OF GOVERNMENT CORNER</b>	
<b>North Quarter</b>	Corner of Section <b>4</b> , Township <b>114</b> , Range <b>45</b>
<b>Fifth</b> Principal Meridian, State of Minnesota, County of <b>Yellow Medicine</b>	
At the corner location shown on the sketch:	
<input checked="" type="checkbox"/>	On <u>Aug 2, 2012</u> found a <u>1/2" x 16" capped rebar RLS # 11943</u> DATE
<input type="checkbox"/>	left monument as found
<input type="checkbox"/>	lowered monument
<input checked="" type="checkbox"/>	removed monument (explain)
<input checked="" type="checkbox"/>	On <u>April 3, 2013</u> placed a <u>Cast iron capped 2" x 30" telspar monument at the location of the found</u> DATE <u>1/2" x 16" capped rebar</u>
<b>Yellow Medicine County Coordinates</b> (1996 Adjustment) N= 164553.02 E= 399374.32	<b>MnDot Project Coordinates</b> (Lyon County Coordinates 1996 Adjustment) N= 290805.00 E= 386374.44
Statement of evidence for this corner location is on back of this page.	
I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Licensed Land Surveyor under the laws of the state of Minnesota.	
Signature <u>[Signature]</u>	Typed or Printed Name: <u>Joshua M. Stern</u>
Date <u>5/1/13</u>	Reg. No. <u>46169</u>

# **STATEMENT OF EVIDENCE**

---

## **North Quarter Corner Section 4, T114N-R45W**

- Oct. 1858 W.J. Neely was contracted by the United States Government Land Office to perform the Original Public Land Survey in this township. He records in his field notes, "Set cor sec post deposited coal made mound Trench & pits as per instructions."
- June 6, 1883 Jonah Peterman, County Surveyor, Records in County Surveyor's Record Book, pg 15 notes a "Stone".
- May 16, 1899 John Norgaard entered into a contract with the Yellow Medicine County Board for the "re-survey of all the section corners except the Township corners" in Yellow Medicine County. "The Monuments are Jasper Granite 2 feet long by 6" by 6", all dimensions are given in feet." John Norgaard turned in his survey field notes to the Yellow Medicine County Recorder, who filed them as Doc No. 28417, on September 28, 1901. These field notes became the County Surveyor's Record Book B page 41.
- Sept. 3, 1934 John Norgaard, County Surveyor, records in the County Surveyor's Record Book, pg 542, a distance from the NE corner of this Section to the west line of the East 1/2 of the NE 1/4, but does not mention if he found a monument at the N1/4 position.
- 1935 MnDOT SP8709 T.H. 68 Book 4, Page 6, Alignments - Land Ties-Topo, shows the 1/16<sup>th</sup> corner to the west of this corner position.
- 1947 MnDOT SP8708 T.H. 68 Book 4, Page 2-10, Alignments - Land Ties, shows the NE corner and the NW corner but does not show any dimensions or angles locating the N 1/4 corner.
- Oct 13, 2011 John Madsen, R.L.S. 13593, while doing survey work in Section 4, shows he "Found a Iron rod in bit. paving (surface)."
- Aug 2, 2012 Joshua M. Stern, Land Surveyor #46169, while doing a remonumentation survey for the Minnesota Department of Transportation located a 1/2" capped rebar with LS 11943 at the surface. He dug a 6.3' deep hole that covered an area extending 5' north, 2.5' south, 3' east, 6' west of the 1/2" capped iron rod location. At a depth of 0.4' a 1/2" x 16" rebar was found upright. At a depth of 5' he found the top of original top soil. Throughout the excavation He came across small field stones, but nothing that appeared to have been set by a surveyor. There is a drainage ditch located just to the south of the corner location, which may answer to the amount of mix and stones located above the original topsoil. A cast iron capped 2" square by 30" long iron telspar monument was placed at the surface at the position of the found 1/2" LS 11943 capped rebar and the 1/2" x 16" capped rebar.