CERTIFICATE OF LOCATION	N OF GOVERNMENT CORNER
NORTH QUARTER Corner of Sect	tion <u>29</u> , Township <u>114 N</u> , Range <u>46 W</u>
5th Principal Meridian, State of Minnesota, County	of Yellow Medicine.
At the corner location shown on the sketch: \[\text{\text{N}} \] On \(\frac{10/25/17}{DATE} \) found a \(\frac{1/2" \text{Rebar}.}{DATE} \)	
On placed a	
SKETCH OF R SET MAG IN SW FACE	REFERENCE TIES
OF TELE GUARD POST	
N61°W 102.477	SET 🖁 REBAR WITH REF CAP
105.47	NZO.E
	<u> </u>
/	180th AVE
	4
SET MAG IN W FACE OF PP	_ _ _
FACE OF FF	
	\\\\\\
	N.T.S.
Statement of evidence for this cor	ner location is on back of this page.
I hereby certify that this document was researched and prepared by me or under my direct supervision and that I am a licensed Lansurveyor under the laws of the State of Minnesota.	Doc# 268182 Fee: \$0.00 2 Pages Property & Public Services Property Records Division Yellow Medicine County, Minnesota I hereby certify that the within instrument was filed on April 5, 2018 at 10:10 AM
Signature	Janel Timm, Yellow Medicine County Recorder By Kuly Kugar Deputy
Title:	
☐ County Surveyor ☐ County Engineer	

STATEMENT OF EVIDENCE:

NORTH QUARTER OF SECTION 29, T114N, R46W, 5TH PM

1871 Corner was originally established by the U.S. General Land Office as a post set in raised mound.

1920 Surveyors Record Book page 436, corner set online and equal distance between Section Corners (2615').

Undated Surveyors Record Book page 457 has ties as follows: Box Elder 12" SE 42.0' Cottonwood 15" NE 39.6'

2008 Roy Marihart completed a survey for Sections 19+20 in which he found a monument at the S1/4 corner Section 20.

2017-10-25 Westwood PS searched the area and found 1/2" rebar, which fits within 1 ft to the 1920 survey distances and also fits the location from 2008 survey. Accepting monument as the corner location and set 3 reference ties.