CERTIFICATE OF LOCATION OF GOVERNMENT CORNER
SOUTH QUARTER Corner of Section 30, Township 115 N., Range 42 W., 5th P.M.
STATE OF MINNESOTA, County of YELLOW MEDICINE.
At the corner location shown on the sketch: □ On found a date
☐ left monument as found, ☐ lowered monument, ☐ removed monument (explain) ☑ On 7-19-2023 placed a 5/8 INCH BY 18" LONG REBAR WITH CAP MARKED date MN LS 48258 AT THE LOCATION SHOWN BELOW.
SKETCH OF REFERENCE TIES
N 1/4 CORNER SEC. 30, T.115, R. 42
½" PIPIE WITH LS 42300 PER DOC. NO. 279682 λ7
NAIL & DISK NAIL & DISK SET 60D SPIKE M- NAIL & DISK 10 10 10 10 10 10 10 10 10 1
SET 60D SPIKE W NAIL & DISK SI CORNER SEC. 30, T.115, R. 42 SET MN LS 48258
S88°40'36"E
2478.21 \$\frac{26.68}{26.68} \frac{22.23}{23.23} \tag{2660.35}
SW CORNER SEC. 30, T.115, R. 42 LS 19092 SET 60D SPIKE W. NAIL & DISK SET 60D SPIKE W. NAIL & DISK SEC. 30, T.115, R. 42 SET MN LS 48258
Minnesota State Plane Coordinate System South Zone, US Feet, Grid Scale 1.0 NAD83 (2011) N = 965661.55 NOT TO SCALE
E = 2114956.60 Statement of evidence relative to this corner location is on back of this page.
I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision. Doc# 280873 Fee: \$0.00 2 Pages Property & Public Services Property Records Division Yellow Medicine County, Minnesota
SIGNATURE Professional Engineer Signature Professional Engineer Signature Professional Engineer By Marit Nordang Deputy Deput

STATEMENT OF EVIDENCE

KLJ contacted the following for survey information

MN GLO/BLM original survey records
Yellow Medicine County Recorder's Office
MNDOT office in Willmar
Yellow Medicine County Highway Engineer's Office
Bonnema Surveys, Inc. of Willmar
O'Malley & Kron Land Surveyors, Inc. of Willmar
Bueltel—Moseng Land Surveying of Marshall
Marihart Surveying, P.A. of Dawson
Egan Field & Nowak, Inc of New Brighton
E.G. Rud & Sons, Inc. of Hutchinson

In September, 1858, C.E. DAVIS & J.W. WEBB JR., General Land Office Deputy Surveyors performing the original survey of the subdivision lines set a wood post, in mound with pits.

In 1917 County Surveyor John Norgaard's "Red Book", page 540, on file at the Yellow Medicine County Recorder's Office shows distances of 2477.00 feet West and 2657.00 feet east to each Section corner. There is no indication of a monument found or set. He notes a fence running south. The fence south is no longer present. There is a fence running north.

On June 7, 2023, KLJ dug a 3x3x3 hole with a large electric jackhammer and generator at the centerline of the road and the extension of the fence line running north and probed and found nothing. KLJ established the South $\frac{1}{4}$ corner location on the centerline of the township road and extension of the fence north.

On July, 19, 2023, KLJ set a \S^n rebar with MN LS 48258 down 0.50' below grade which falls on the centerline of the township road and extension of the fence north.