CERTIFICATE OF LOCATION OF GOVERNMENT CORNER	
SOUTHEAST Corner of Section 30, Township 115 N., Range 42 W., 5th P.M.	
STATE OF MINNESOTA, County of YELLOW MEDICINE.	
At the corner location shown on the sketch:  □ On found a  date	
☐ left monument as found, ☐ lowered monument, ☐ removed monument (explain)	
☑ On	
date	
MN LS 48258 AT THE LOCATION SHOWN BELOW.	
SKETCH OF REFERENCE TIES	
1-8-1	
	E ¼ CORNER SEC. 30, T.115, R. 42
	SET MN LS 48258
l	$\mid \cdot \mid$
  -90'	66
5.00	657
S‡CORNER SET 60D SPIKE W.	SE CORNER SEC. 30, T.115, R. 42
SEC. 30, T.115, R. 42 NAIL & DISK SET MN LS 48258	SET MN LS 48258
S88°40'24"E - 38	SET MASON NAIL
2660.35	IN TOP OF 18"
CMP CULVERT	
SET NAIL & DISK	<b>*</b> * *
IN SE FACE OF POWER POLE UP 3.0'.	SET MASON NAIL
	IN TOP OF 18"
	CMP CULVERT
Minnesota State Plane Coordinate System	
South Zone, US Feet, Grid Scale 1.0	
NAD83 (2011) N = 965599.96	NOT TO COME
E = 2117616.24	NOT TO SCALE
Statement of evidence relative to this corner location is on back of this page.	
I hereby certify that this document and the data	
contained herein was prepared by me or under my	Doc# 280874 Fee: \$0.00 2 Pages Property & Public Services
direct supervision.	Property Records Division
1 m / 9-5-2022	Yellow Medicine County, Minnesota I hereby certify that the within instrument
SIGNATURE DATE	was filed on September 11, 2023 at 12:20 PM
Registration No. <u>48258</u>	Janel Timm, Yellow Medicine County Recorder
☑ Land Surveyor ☐ Professional Engineer	By Marit Nordang Deputy
☐ County Surveyor ☐ County Engineer	0 . ,

## STATEMENT OF EVIDENCE

KLJ contacted the following for survey information

MN GLO/BLM original survey records
Yellow Medicine County Recorder's Office
MNDOT office in Willmar
Yellow Medicine County Highway Engineer's Office
Bonnema Surveys, Inc. of Willmar
O'Malley & Kron Land Surveyors, Inc. of Willmar
Bueltel—Moseng Land Surveying of Marshall
Marihart Surveying, P.A. of Dawson
Egan Field & Nowak, Inc of New Brighton
E.G. Rud & Sons, Inc. of Hutchinson

In September, 1858, C.E. DAVIS & J.W. WEBB JR., General Land Office Deputy Surveyors performing the original survey of the subdivision lines set a wood post, in mound with pits.

In November, 1917 County Surveyor John Norgaard's "Red Book", page 395, on file at the Yellow Medicine County Recorder's Office shows distances of 2656.00 feet East and 2659.00 feet North to each Section corner. There is no indication of a monument found or set.

In 1917 County Surveyor John Norgaard's "Red Book", page 540, on file at the Yellow Medicine County Recorder's Office shows distances of 2657.00 feet West and 2647.00 feet South to each Section corner. There is no indication of a monument found or set.

On June 7, 2023, KLJ dug and found a 60d spike down 0.50' on centerline/centerline of the township road intersection. The spike was lifted and no other magnetic draws were present. The 60d spike was reset and accepted as the Southeast Section corner. All Highway Department ties are gone.

On July, 19, 2023, KLJ removed the 60d spike and set a  $\frac{\pi}{8}$  rebar in the same location as the 60d spike with MN LS 48258 down 0.50' below grade which falls on the centerline intersection of the township road.