	CERTIFICATE OF LOCATION OF GOVERNMENT CORNER
	EAST QUARTER Corner of Section 30, Township 115 N., Range 42 W., 5th P.M.
	STATE OF MINNESOTA, County of <u>YELLOW MEDICINE</u> .
	At the corner location shown on the sketch:  On found a  date
	☐ left monument as found, ☐ lowered monument, ☐ removed monument (explain)  ☐ On
•	SKETCH OF REFERENCE TIES
	SET NAIL & DISK- IN NE FACE OF POWER POLE UP 3.0'.  NE CORNER SEC. 30, T.115, R. 42  1
	W 1 CORNER SEC. 30, T.115, R. 42 SET MN LS 48258
	S88°49'20"E 5151.76  S88°49'20"E 5151.76  SEC. 30, T.115, R. 42 SET MN LS 48258
	SET NAIL & DISK- IN SE FACE OF SOUTH POWER POLE UP 3.5'.  SET 60D SPIKE W. NAIL & DISK  NAIL & DISK
	Minnesota State Plane Coordinate System South Zone, US Feet, Grid Scale 1.0 NAD83 (2011) N = 968256.29  NOT TO SCALE
	E = 2117709.09  Statement of evidence relative to this corner location is on back of this page.
4	I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.  Doc# 280875 Fee: \$0.00 2 Pages Property & Public Services Property Records Division Yellow Medicine County, Minnesota I hereby certify that the within instrument was filed on September 11, 2023 at 12:25 PM
	Registration No. 48258    Janel Timm, Yellow Medicine County Recorder   By Warit Nordang Deputy
	☐ County Surveyor ☐ County Engineer ☐ County Engineer ☐ Deputy

## STATEMENT OF EVIDENCE

KLJ contacted the following for survey information

MN GLO/BLM original survey records
Yellow Medicine County Recorder's Office
MNDOT office in Willmar
Yellow Medicine County Highway Engineer's Office
Bonnema Surveys, Inc. of Willmar
O'Malley & Kron Land Surveyors, Inc. of Willmar
Bueltel—Moseng Land Surveying of Marshall
Marihart Surveying, P.A. of Dawson
Egan Field & Nowak, Inc of New Brighton
E.G. Rud & Sons, Inc. of Hutchinson

In September, 1858, C.E. DAVIS & J.W. WEBB JR., General Land Office Deputy Surveyors performing the original survey of the subdivision lines set a wood post, in mound with pits.

In November, 1917 County Surveyor John Norgaard's "Red Book", page 395, on file at the Yellow Medicine County Recorder's Office shows distances of 2657.00 feet North and 2657.00 feet South to each Section corner. The plat shows a stone. The notes indicates he set a stone on a straight line single proportion.

On June 7, 2023, KLJ dug a 3x3x3 hole with a large electric jackhammer and generator at the midpoint and online between section corners north and south and probed and found nothing. KLJ established the East  $\frac{1}{4}$  corner location at the straight line single proportion between section corners north and south.

On July, 19, 2023, KLJ set a  $\S$ " rebar with MN LS 48258 down 0.50' below grade which falls on the centerline of the township road.