CERTIFICATE OF LOCATION	OF GOVERNMENT CORNER
NORTH QUARTER Corner of Section 27, Township 115 N., Range 41 W., 5th P.M.	
STATE OF MINNESOTA, County of YELLOW MEDICINE.	
At the corner location shown on the sketch:	
On found a	
☐ left monument as found, ☐ lowered monument, ☐ removed monument (explain)	
☑ On	
MN LS 48258 AT THE LOCATION SHOWN BELOW.	
SKETCH OF REFERENCE TIES	
SET 60D SPIKE W:	Ą
NAIL & DISK	N
	N 4 CORNER SEC. 28, T.115, R. 41
	SET MN LS 48258
12-	SET 60D SPIKE W.
SET 60D SPIKE W. NAIL & DISK	
S88°35'40"E	
2684.13	<u>\$88°35'40"E</u> 2684.13
NW CORNER 17.90	
SEC. 27, T.115, R. 41 1" PIPE W SEAL 43844 SET 60D SPIKE W.	NE CORNER
PER DOC. NO. 245313 NAIL & DISK	SEC. 27, T.115, R. 41 5" REBAR W SEAL 11943
N01°13'57'	·
1001	
Minnesota State Plane Coordinate System   1	S 1/4 CORNER
South Zone, US Feet, Grid Scale 1.0 NAD83 (2011)	SEC. 27, T.115, R. 41 FOUND 1" PIPE W LS 11943
N = 969913.44 E = 2162768.06	NOT TO SCALE
Statement of evidence relative to this corner location is on back of this page.	
I hereby certify that this document and the data	
contained herein was prepared by me or under my direct supervision.	Doc# 280882 Fee: \$0.00 2 Pages Property & Public Services
	Propertý Records Division Yellow Medicine County, Minnesota
SIGNATURE DATE	I hereby certify that the within instrument was filed on September 11, 2023 at 1:00 PM
Registration No. 48258	janel Timm, Yellow Medicine County Recorder
☑ Land Surveyor ☐ Professional Engineer	a Marit Nordana
☐ County Surveyor ☐ County Engineer	Deputy

## STATEMENT OF EVIDENCE

KLJ contacted the following for survey information

MN GLO/BLM original survey records
Yellow Medicine County Recorder's Office
MNDOT office in Willmar
Yellow Medicine County Highway Engineer's Office
Bonnema Surveys, Inc. of Willmar
O'Malley & Kron Land Surveyors, Inc. of Willmar
Bueltel—Moseng Land Surveying of Marshall
Marihart Surveying, P.A. of Dawson
Egan Field & Nowak, Inc of New Brighton
E.G. Rud & Sons, Inc. of Hutchinson

In September, 1858, C.E. DAVIS & J.W. WEBB JR., General Land Office Deputy Surveyors performing the original survey of the subdivision lines set a wood post, in mound with pits.

Date not shown, County Surveyor "Brown Book", page 15, on file at the Yellow Medicine County Recorder's Office shows distances of 5361 feet across the north line of the Section, no display of any monuments shown or noted.

In April, 1918 County Surveyor John Norgaard's "Red Book", page 401, on file at the Yellow Medicine County Recorder's Office shows distances of 2682 feet East and 2682 feet West to each Section corner. The notes state that he set a stake on line and equal distances between section corners.

On July, 19, 2023, KLJ found a 60d spike down 0.50 below grade on the centerline of the road, the spike was lifted and no other magnetic draws were present. KLJ then dug a 3x3x3 hole with a large electric jackhammer and generator at the spikes location which was midpoint and online between section corners east and west and probed and found nothing. KLJ found no evidence of the original corner or other corner monuments. KLJ established the location at the straight line single proportion which falls on the centerline of the township road and field division south. Monument set 0.50' below grade.